

### ULTRA-MATE® BRAND HTH HOOK

ULTRA-MATE® brand HTH fasteners offer performance properties never before available with ordinary hook and loop fasteners. They are moulded hook fasteners engineered to provide superior closure with a variety of loops, and to meet specific performance characteristics in conjunction with a range of polymers, each of which provides it's own distinctive features. As such, each HTH hook style differs from each other. Each has its own specific characteristics and advantages to better meet your specific fastening requirements.

#### HOOK STYLE 705

A moulded nylon hook which is similar to our "Sew On" product in its properties, but with the added benefit of being low linting.

- Nylon hook
- High cycle: excellent memory for long life.
- Low density
- Melting Point: 173°C

#### HOOK STYLE 711

Is a high density polyethylene moulded hook ideal on disposable items and can be gamma ray sterilised, which is ideal for medical applications.

- Polyethylene hook.
- Medium cycle: medium life.
- Low cost.
- Melting Point: 136°C

SPECIFICATIONS		
COLOUR	25mm	50mm
BLACK	•	•
WHITE	•	•
ADHESIVE BACKING	Sew on and Adhesive 0119	
PACKAGING:	Hook style 711 is adhesive backed: 22.8 metres rolls.	
	Hook style 705 Sew on: 45.6 metres.	
	Hook style 705 Adhesive: 22.8 metres.	
<i>Before using adhesives in production, the user should test the adhesive to determine the suitability for the intended use.</i>		

HOOK AND LOOP CLOSURE PERFORMANCE						
WHEEL CYCLE LIFE IN PEEL MODE.	SHEAR STRENGTH LENGTH WISE. P.S.I. AVERAGE	SHEAR STRENGTH WIDTH WISE. P.S.I. AVERAGE	CURVED SHEAR ON 4 1/2" RADIUS P.S.I. AVERAGE	TENSION OR LATCHING EFFECT P.S.I. AVERAGE	PEEL STRENGTH LENGTH WISE. P.I.W. AVERAGE	
HTH 705: HIGH	HTH 705: 17	HTH 705: N/A	HTH 705: 34	HTH 705: N/A	HTH 705: 1.6	
HTH 711: MED.	HTH 711: 34	HTH 711: N/A	HTH 711: 68	HTH 711: N/A	HTH 711: 2.1	

**IMPORTANT NOTICE TO PURCHASER**

All statements, technical advice and recommendations contained herein are based on tests believed to be reliable, but the accuracy thereof is not guaranteed, and the following is made in lieu of all warranties, expressed or implied: Seller's and manufacturer's only obligation shall be to replace the quantity of product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. Before using, user shall determine the suitability of the product for its intended use, and user assumes all risk and liability whatsoever in connection therewith. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of seller and manufacturer.



**VELCRO AUSTRALIA. PTY LTD.**

5 - 11 David Lee Road, Hallam Victoria. 3803.

Phone: (03) 9703 2466 Fax: (03) 9703 2305

Free Call: 1800 337 024

[www.velcro.com.au](http://www.velcro.com.au)

*Quality*  
*Service*  
*Innovation*