







## VELSTUD® BRAND FASTENERS

A moulded nylon square with a protruding insertion shank. The square surface has a permanently attached VELCRO® brand loop or moulded hook fastening surface.

Method of Attachment: Shank insertion into pre-drilled hole.

These can be easily and quickly attached to most rigid surfaces. It can also be mated with other VELCRO® brand hook or loop tape products. Its design provides exceptional added-value to your products and your business.

SPECIFICATIONS	
STANDARD FACE WIDTH:	STANDARD STUD LENGTH:
25.4mm x 25.4mm (1"x1")	12.7mm (1/2")
Standard stud diameter: 9.5mm (3/8")	Available colours: Black only
VELSTUD® BRAND FASTENERS PROPERTIES INCLUDE:	
<ul style="list-style-type: none"> <li>• Its impressive holding power.</li> <li>• Being tough and durable, providing long time dependability.</li> <li>• Improving design flexibility - for parts consolidation, future disassembly and recycling.</li> <li>• Simplifying and speeding assembly, making automotive use more practical.</li> <li>• Reducing overall cost-labour and OHS issues.</li> <li>• Helping to eliminate squeaks and rattles, thereby enhancing customer satisfaction.</li> <li>• VELSTUD® brand - Hook: Truck trim and panels. Scrubber attachment of floor polishers</li> <li>• VELSTUD® brand - Loop: baby's car seat trimming.</li> </ul>	

HOOK AND LOOP CLOSURE PERFORMANCE					
WHEEL CYCLE LIFE IN PEEL MODE.	SHEAR STRENGTH LENGTH WISE. P.S.I. AVERAGE	SHEAR STRENGTH WIDTH WISE. P.S.I. AVERAGE	CURVED SHEAR ON 4 1/2" RADIUS P.S.I. AVERAGE	TENSION OR LATCHING EFFECT P.S.I. AVERAGE	PEEL STRENGTH LENGTH WISE. P.I.W. AVERAGE
					
LOW	22	11	N/A	12	2.5

**IMPORTANT NOTICE TO PURCHASER**

All statements, technical advice and recommendations contained herein are based on tests believed to be reliable, but the accuracy thereof is not guaranteed, and the following is made in lieu of all warranties, expressed or implied: Seller's and manufacturer's only obligation shall be to replace the quantity of product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. Before using, user shall determine the suitability of the product for its intended use, and user assumes all risk and liability whatsoever in connection therewith. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of seller and manufacturer.



*Quality*  
*Service*  
*Innovation*